

Product Information

MRL-3

Interdynamics R-134a Super Seal Metal and Rubber A/C repair kit with leak detector



Product Information:

WITHIN REASON, this product will repair the SMALL hard to find porous A/C leaks on:

- Evaporator, Condenser, Compressor, Accumulator and Receiver/Dryer
- O-Rings, Gaskets and Hoses.

Important:

- SUPER SEAL WILL NOT REPAIR A VISIBLE HOLE OR A SPLIT IN ANY A/C COMPONENTS.

How to use guide:

1

Using the R-134a refrigerant GL1 with the colour coded charging gauge or QC1HD with the RFT134A for the trade, connect the quick coupler to the Low-Side Charging Port, take a pressure reading then add enough refrigerant to enable the compressor to engage, "click in".

2

Swap to the Super Seal product, connect again to the same low-side port and add the whole can, shake well until empty then disconnect the Super Seal.

3

Immediately reconnect the quick coupler of the Interdynamics GL1 with the colour coded charging gauge or QC1HD with the RFT134A and carry on recharging/topping-up the system with refrigerant until the gauge needle stabilises in the BLUE zone.

Important:

- THE SUPER SEAL PRODUCT WORKS VERY QUICKLY, SO TO PREVENT THE SUPER SEAL FROM SEALING THE CHARGING PORT THE SYSTEM MUST BE RECHARGED/TOPPED-UP IMMEDIATELY!
- IF YOU HAVE A VISIBLE HOLE OR A SPLIT IN ANY COMPONENT IT WILL NEED TO BE REPLACED, THE SYSTEM PRESSURE TESTED, VACUUMED AND RECHARGED USING PROFESSIONAL EQUIPMENT.



J&S Automotive Distributors

Unit 17, Park West Road, Park West, Dublin 12

AUTOMOTIVE

t 01-629 7999 f 01-620 5664 e sales@jsautomotive.ie

www.id-europe.co.uk
for FREE Tutorials